

COOL IT – WITH EBERSPÄCHER INSULATED CONTAINERS FOR PROFESSIONAL APPLICATIONS





EUROENGEL

THE MOBILE COMPRESSOR REFRIGERATION CONTAINERS

Our compressor refrigeration containers are the flexible, convenient solution for professional users who have to transport perishable goods on-board standard cars or vans, whilst still complying with food hygiene standards.

The heavy duty containers are made of rotationally moulded polyethylene and can be cleaned easily according to 93/43/EEC (HACCP). Operating voltage is 12-24V DC and 100-240V AC, 50-60Hz. The refrigerant gas is CFC free R134a.

The digital temperature controller allows an easy setting of the required internal temperature and the control of the true internal temperature.

Furthermore, all mobile compressor refrigeration containers can also be equipped with a heating function, e.g. to transport warm food, or to transport temperature sensitive goods at positive temperatures in below zero ambient conditions.

APPLICATIONS INCLUDE

- **Pharmaceutical** – Transport of insulin / vaccines, etc.
- **Medical** – Clinical trials, blood, organ transport, etc.
- **Laboratory** – Water samples, DNA, etc.
- **Military** – Green and sand coloured versions available.
- **Food and Drink Industry** – Samples, vending machine stockists, catering, etc.



The units were positively tested by TÜV SÜD according to EN 55014-1:2006, EN 61006-6-2:2005, EN 60335-2-24/A2:2007 and bear the CE and the TÜV SÜD “production monitored, safety tested” certification mark.


C T0022 FDN -24°C H T0022 FDH +40°C > -24°C
Top Loader – 22 Litre

-24°C (+30°C Ambient Temperature)	Weight: 17kg
12 – 24V DC, 9 – 4 Amp	Dimensions mm (W x D x H)
100 – 240V AC, 1.6 – 0.8A, 50 – 60Hz	Outside: 590 x 380 x 480
65 – 70mm PU* K<0.40 Wm²K	Inside: 290 x 230 x 350


C T0032 FDN -24°C H T0032 FDH +40°C > -24°C
Top Loader – 32 Litre

-24°C (+30°C Ambient Temperature)	Weight: 19kg
12 – 24V DC, 9 – 4 Amp	Dimensions mm (W x D x H)
100 – 240V AC, 1.6 – 0.8A, 50 – 60Hz	Outside: 670 x 390 x 480
65 – 70mm PU* K<0.40 Wm²K	Inside: 360 x 250 x 350


C T0056 FDN -24°C H T0056 FDH +40°C > -24°C
Top Loader – 56 Litre

-24°C (+30°C Ambient Temperature)	Weight: 26kg
12 – 24V DC, 9 – 4 Amp	Dimensions mm (W x D x H)
100 – 240V AC, 1.6 – 0.8A, 50 – 60Hz	Outside: 800 x 500 x 500
70mm PU* K<0.40 Wm²K	Inside: 450 x 330 x 350


C T0082 FDN -24°C H T0082 FDH +40°C > -24°C
Top Loader – 82 Litre

-24°C (+30°C Ambient Temperature)	Weight: 29kg
12 – 24V DC, 9 – 4 Amp	Dimensions mm (W x D x H)
100 – 240V AC, 1.6 – 0.8A, 50 – 60Hz	Outside: 940 x 560 x 550
80mm PU* K<0.40 Wm²K	Inside: 540 x 370 x 360


C F0140 NDN -10°C C F0140 FDN -21°C H F0140 NDH +30°C > -10°C
Front Opening – 140 Litre

NDN: -10°C (+30°C Ambient Temperature)	Weight: 40kg (FDN: 45kg)
FDN: -21°C (+30°C Ambient Temperature)	Dimensions mm (W x D x H)
12 – 24V DC, 9 – 4 Amp (FDN: 18 – 9A)	Outside: 1000 x 620 x 710
100 – 240V AC, 1.6 – 0.8A, 50 – 60Hz	Inside: 620 x 410 x 510
80 – 100mm PU* K<0.40 Wm²K	


C F0330 NDN +0°C C F0330 FDN -21°C H F0330 NDH +30°C > +0°C
Front Opening – 330 Litre

NDN: +0°C (+30°C Ambient Temperature)	Weight: 90kg
FDN: -21°C (+30°C Ambient Temperature)	Dimensions mm (W x D x H)
12 – 24V DC, 9 – 4 Amp (FDN: 18 – 9A)	Outside: 1020 x 1000 x 910
100 – 240V AC, 1.6 – 0.8A, 50 – 60Hz	Inside: 810 x 610 x 660
100mm PU* K<0.40 Wm²K	


C F0750 NDN +0°C C F0785 NDN +0°C C F0915 NDN +0°C
Front Opening with Side Door – 750 Litre / 785 Litre / 915 Litre

+0°C (+30°C Ambient Temperature)	Weight (F0915): 160kg
12 – 24V DC, 18 Amp	Dimensions mm (W x D x H)
100 – 240V AC, 1.0 – 0.6A, 50 – 60Hz	Outside (F0915): 1200 x 1500 x 1180 (F0750): Reduced Outside Height of 980 (F0785): Reduced Outside Width of 1080
130mm PU* K<0.28 Wm²K	Inside (F0915): 930 x 930 x 830

THE COMPREHENSIVE EBERSPÄCHER PRODUCT RANGE ALSO INCLUDES HEATING, AIR CONDITIONING AND REFRIGERATION SYSTEMS FOR COMMERCIAL VEHICLES, CARS, BUSES, COACHES, MOTORHOMES, CARAVANS, MARINE, OFF-HIGHWAY AND MILITARY APPLICATIONS.

MORE INFORMATION IS AVAILABLE FROM ONE OF OUR 5,000 SERVICE PARTNERS WORLDWIDE.

AUTHORISED DEALER

Eberspächer (UK) Ltd
Headlands Business Park
Salisbury Road, Ringwood
Hampshire BH24 3PB
Tel: 01425 480151
Fax: 01425 480152
enquiries@eberspacher.com
www.eberspacher.com

