

MOBILE HANDWASH FOR MOBILE PEOPLE

HOT AND COLD WATER AT ANY LOCATION IS NOW AN AFFORDABLE REALITY



Eberspächer are proud to announce what is undoubtedly the most compact, easy to install and technologically advanced mobile handwash unit. We now feature fully automatic versions of both Handiwash and Miniwash, making installation even easier.

For anyone whose work brings them into contact with hazardous substances, or unhygienic conditions, it should be considered a necessity.

Extensively used by major companies, Eberspächer Handwash Units can assist you in meeting occupational health and safety requirements.

APPLICATIONS INCLUDE

- Mobile tradespeople.
- Professional field workers.
- Maintenance workers.
- Food vendors.
- Utility vehicle users.
- Off-road enthusiasts.
- Campers.
- Anglers.

Eberspächer Handiwash units carry a full 36 months warranty.

Handiwash is type approved and **CE** approved.

Conforms to ELV directives.



NEW 12V "SMART" version for vehicles with start-stop technology now available

HIGH IMPACT HOUSING

Moulded from tough, UV resistant polymers suitable for internal and external applications.

LOW POWER, HEAVY DUTY HEATER ELEMENT

Using high corrosion resistant materials and state of the art electronics, the heater element thermostatically controls water temperature to 60°C. The system is also protected by a thermal overload safety device.

EASY INSTALLATION

Unit can be easily mounted to any vertical surface and wired to a 12 Volt power source, 24 Volt systems are available.

Optional lift out bowl available on both models.

APPLICATION AND TECHNICAL DATA

STANDARD UNIT

- Manual on/off switch and relay required (not supplied).
- Relay must be triggered by engine run or ignition signal.
- Operator has full control of operation.


PART NUMBER	DESCRIPTION
29.2100.01.6416	Miniwash 12V Standard
29.2100.01.6331	Handiwash 12V Standard

AUTO SMART RELAY

- Direct connection to vehicle battery.
- No additional relay or switch required.
- Automatic operation when alternator is charging (engine running).
- Automatically switches off, after timed delay, when engine is switched off.
- Especially developed for stop/start vehicles or those with intelligent alternators having battery voltage levels between 12V and 15V.
- Can be used on standard alternator type vehicles.

PART NUMBER	DESCRIPTION
29.2100.16.1023	Miniwash 12V + Auto Smart Relay
29.2100.16.1025	Handiwash 12V + Auto Smart Relay


Handiwash Fully automatic units are available.



Dimensions: 300 (width), 230 (depth), 405 (total width), 520 (height)

Water capacity – 8.5 litres	Water level sight glass
Hot and Cold water and taps	Low power consumption
10 Amps @ 12 Volt	7.2 Amps @ 24 Volt
Hot water temperature 60°C	

Miniwash Fully automatic units are available.



Dimensions: 300 (width), 222 (depth), 400 (total width), 390 (height)

Water capacity – 6.0 litres	Water level sight glass
Hot water and taps only	Low power consumption
9.6 Amps @ 12 Volt	7.2 Amps @ 24 Volt
Hot water temperature 49°C	

Eberspächer (UK) Ltd

Climate House, Yeoman Road

Ringwood, Hampshire BH24 3FA

Tel: 01425 480151 – Fax: 01425 480152

enquiries@eberspaecher.com – www.eberspaecher.com