

MILITARY COOLING – IN A BOX





MILITARY CONTAINER COOLING

Our compressor refrigeration containers are the flexible, convenient solution for professional users who have to transport perishable goods on-board standard cars or vans, whilst still complying with food hygiene standards.

The heavy duty containers are made of rotationally moulded polyethylene and can be cleaned easily according to 93/43/EEC (HACCP). Operating voltage is 12-24V DC and 100-240V AC, 50-60Hz. The refrigerant gas is CFC free R134a.

The digital temperature controller allows an easy setting of the required internal temperature and the control of the true internal temperature.

Furthermore, all mobile compressor refrigeration containers can also be equipped with a heating function, e.g. to transport warm food, or to transport temperature sensitive goods at positive temperatures in below zero ambient conditions.

- Essential medical requirements i.e. Blood transportation.
- Food and liquids.
- Used in many worldwide applications.
- Available in a variety of sizes.
- Voltages: 12 and 24 volt DC, 240 volt AC.

The units were tested by TÜV SÜD according to EN 55014-1:2006, EN 61006-6-2:2005, EN 60335-2-24/A2:2007 and bear the CE and the TÜV SÜD "production monitored, safety tested" certification mark.



C T0032 FDN -24°C H T0032 FDH +40°C > -24°C

Top Loader – 32 Litre

-24°C (+30°C Ambient Temperature)	Weight: 19kg
12 – 24V DC, 9 – 4 Amp	Dimensions mm (W x D x H)
100 – 240V AC, 1.6 – 0.8A, 50 – 60Hz	Outside: 670 x 390 x 480
65 – 70mm PU* K<0.40 Wm²K	Inside: 360 x 250 x 350



C T0056 FDN -24°C H T0056 FDH +40°C > -24°C

Top Loader – 56 Litre

-24°C (+30°C Ambient Temperature)	Weight: 26kg
12 – 24V DC, 9 – 4 Amp	Dimensions mm (W x D x H)
100 – 240V AC, 1.6 – 0.8A, 50 – 60Hz	Outside: 800 x 500 x 500
70mm PU* K<0.40 Wm²K	Inside: 450 x 330 x 350

C = Cooling only. **H** = Heating & Cooling. PU* = Walls filled with polyurethane rigid foam.

Eberspächer (UK) Ltd
 Climate House
 Yeoman Road, Ringwood
 Hampshire BH24 3FA
 Tel: 01425 480151
 Fax: 01425 480152
 enquiries@eberspaecher.com
 www.eberspaecher.com

